

Sinterit Lisa 2

Benchtop SLS 3D printer - product specification



GENERAL INFORMATION	
Status	September 2018
Technology	SLS
Laser system	IR Laser Diode 5 [W]; $\lambda = 808$ [nm]
Dimensions	690 x 500 x 880 [mm] (27.1 x 19.7 x 34.6 [in])
Weight	90,0 [kg] (198 [lbs])
PRINT VOLUME	
Max size of print diagonally ⁰	316 [mm] (12.4 [in])
Flexa - high accuracy max print volume	110 x 160 x 250 [mm] (4.3 x 6.2 x 9.8 [in])
PA - high accuracy max print volume	90 x 120 x 230 [mm] (3.5 x 4.7 x 9 [in])
PRINTER PARAMETERS	
Size of Print Bed	150 x 200 x 260 [mm] (5.9 x 7.9 x 10.2 [in])
XY accuracy	from 0,05 [mm] (0.002 [in])
The layer height Z (min.-max.)	0,075 - 0,175 [mm] (0.003 - 0.007 [in])

Informations provided within this document are typical values for reference and comparison only. Parameters presented in this specification are subject to change. Final part properties may vary based on printed part design and print orientation.

PRINT FEATURES	
Min. wall thickness	from 0,4 [mm] (0.015 [in])
Min. detail size	from 0,1 [mm] (0.003 [in])
Hole Diameter	from 0,5 [mm] (0.019 [in])
Moving Part Clearance	from 0,2 [mm] (0.007 [in])
ADDITIONAL PRINTER FEATURES	
Nitrogen chamber	Built-in
Coupling installed in Lisa 2	Pneumatic quick-coupling Male Plug Nipple DN7.2
Average Nitrogen consumption	0,15 [m ³ /hour]
MATERIALS	
Powder PA11 - polyamide 11	15-76 [µm] (0,59 - 3 [mil]), average size 40 [µm] (1,6 [mil])
Powder PA12 Smooth - polyamide 12	20-100 [µm] (0,79 - 3,94 [mil]), average size 38 [µm] (1,5 [mil])
Powder Flexa Black	20-105 [µm] (0,79 - 4,13 [mil])
Powder Flexa Grey	20-105 [µm] (0,79 - 4,13 [mil])
Nitrogen use materials	In progress
Material refreshing ratio ¹	from 0 - 50 % depending on the material
SOFTWARE	
Software ²	Sinterit Studio 2018
Supported file types	STL, OBJ, 3DS, FBX, DAE, 3MF
OS compatibility	Microsoft Windows
COMMUNICATION	
LCD screen	Capacitive, color
Touchscreen	7 [in]
On-board camera	Built-in
Connectivity	Wifi, Usb port
HEATING SYSTEM	

Informations provided within this document are typical values for reference and comparison only. Parameters presented in this specification are subject to change. Final part properties may vary based on printed part design and print orientation.

Independent	Heated: piston, cylinder, Feed Bed, Print Bed
Max. temperature in the chamber	200 [°C] / 392 [°F]
POWER	
Power supply	220-240 [V] AC, 50/60 [Hz], 7 [A] or 100-130 [V] AC, 50/60 [Hz], 15 [A]
Average power consumption	1 [kW]
Maximum power consumption	1,8 [kW]
PACKAGING	
Package contains	LISA 2 3D printer + Set of Accessories + Manual
WARRANTY	One year limited warranty

⁰ Max size of print diagonally depend on the type of material.

¹ Material refreshing ratio - percent of Fresh powder which has to be mixed with Used (unsintered) powder - to be reused to the next print.

² Technical requirements to install Sinterit Studio Software:

- Windows 7 or higher,
- Minimum 500 MB of disc space,
- Minimum 2 GB of RAM,
- Graphics adapter compatible with OpenGL 3.0 or higher.



Informations provided within this document are typical values for reference and comparison only. Parameters presented in this specification are subject to change. Final part properties may vary based on printed part design and print orientation.



Kit Lisa 2
 Impresora SLS Lisa 2
 Sinterit Sandbaster
 Sinterit Sieve
 Sinterit PA12 Smooth
 6 Kg Power (2 kg Print ready printer+ 4 Fresh Power)
 2 Kg Flexa Black

